

SCN-USBR.02

KNX USB Interface, 2 SU MDRC



Product description:

The MDT USB interface enables local programming and diagnosis of the KNX bus.

Product functions:

- for bidirectional connection between PC and KNX Bus via USB
- Compatible to ETS 4/5/6
- **Supports PC Sleep mode**
- **For updating KNX devices**
- Fast application download (long frame support as of ETS 5)
- 3 year warranty

Technical data:

Device	Device type	SCN USB Interface
	Article Number	SCN-USBR.02
	EAN / GTIN	4251916100094
	Installation width	2 SU / 36 mm
	Dimensions (H x W x D)	90 x 36 x 72 mm
	Weight, gross (incl. packaging)	0.085 kg
	Protection classification	IP20
	Installation type	MDRC, DIN rail 35 mm
	Installation position	any
	Weight, net	0.066 kg
KNX	Nominal voltage KNX	30 V DC SELV
	Voltage range KNX	21 ... 31 V DC SELV
	Typical power consumption KNX bus	< 0,3 W
	KNX Medium	TP-256 with long frame support
	KNX Application	as of ETS 3
Environmental conditions	Ambient operating temperature	0 ... 45 °C
	Storage	-20 ... +55 °C
	Humidity	< 95 %
Connections	Connection type	USB type B, socket
	KNX connection type	KNX terminal
	KNX cable cross section	0.6 ... 0.8 mm, solid conductor

Wiring diagram:

